

Portable Four Hour Fire Rated and Insulated Lithium Battery Storage and Charging Unit.

10'6" X 8'0" X 9'0" High Exterior
9'0" X 7'0" X 7'0" High Interior
Interior and Exterior Two Part Chemical Resistant Epoxy Paint with Exterior Urethane Top Coat
6" Deep Secondary Containment Area with Removable Galvanized Grating and Grating Supports
3 Hour Fire Rated Self Closing 5'0" Wide X 6'8" High Double Door with Keyed Lock and Interior Safety Release
12 X 12 Vents Sized for 6 Air Changes Per Hour Natural Ventilation Protected by 3 Hour Fire Rated Dampers and Adjustable Vent Covers
Forklift Pockets and Tie Down Plates
6 Rows of 16" Deep Adjustable Shelving with 1" Lip on All Edges
Explosion Proof Interior Light with Exterior Switch, Explosion Proof Exhaust Fan with Exterior Switch.
Hazardous Location 14,000 BTU Air Conditioner and 12,000 BTU Thermostat with Integrated Thermostat. 4 Each Hazardous Location Receptacles with Plug Adapters. Hazardous Location Panic Push Button with Exterior Alarm Bell
Exterior 100 Amp NEMA 3R Load Center with Exterior Weatherproof Receptacle
Dry Chemical Fire Suppression System



Ideal Environmental Products & Services

1725 W. Pacheco Blvd., Los Banos, CA 93635 800-844-6998 209-752-3177

www.CHEM-STOR.com Email: ideal.sales@chem-stor.com

CHEM-STOR